



Cali Vinyl™ Flooring



**Care & Maintenance**

(844) 293-6060  
Distributed by Bamboo-Design.ca

## After Install/Floor Care Maintenance:

**Note: For the most up-to-date warranty information, please visit [www.Bamboo-Design.ca](http://www.Bamboo-Design.ca)**

- For Cleaning, we recommend dry or damp mopping as needed using Bona Stone Tile & Laminate cleaner or similar.
- To clean up dried glue use Bostik's Ultimate Adhesive remover.
- Do not use anything abrasive or harsh chemicals to clean the floor. Never use any of the following products on your floor: ammonia-based cleaners, mineral spirits, acrylic finishes, wax-based products, detergents, bleach, polishes, oil soap, abrasive cleaning soaps, acidic materials such as vinegar.
- Never apply wax treatments or top coats to the floor.
- Do not drag furniture across the floor, use felt pads on chair and furniture legs.
- Equip swiveled-type office chairs or rolling furniture with broad surface non-staining casters with a diameter of at least 2".
- Keep pet's nails trimmed to avoid excess scratching.
- Lighter colors and darker colors naturally show more dirt, flaws and marks and are considered higher maintenance.
- Sweep or vacuum the floor regularly to remove loose dirt. Do NOT use vacuums that use a beater bar or turn beater bar off.
- Place quality walk-off mats at all entrances to retain tracked in dirt, grit and moisture, never use latex or rubber backed mats as they can permanently stain the floor.
- Area rugs are also recommended in front of kitchen sinks and in high traffic areas.
- Although the Cali Vinyl™ Plank Flooring is waterproof, it is still a best practice to avoid excessive moisture on the floor. Therefore, we recommend soaking up spills immediately using a dry towel or dry mop.
- Limit direct sunlight on floor by using curtains and blinds in areas that are exposed to high UV rays.
- Heating units or non-insulated ductwork close to the flooring or subfloor may cause "hot spots" which must be eliminated prior to installation.
- Heavy furniture (500+ lbs.) may obstruct the free, natural movement of a floated floor. Restricting this movement in certain areas can lead to problems such as buckling or separation when the floor experiences natural expansion and/or contraction.
- When moving large appliances use proper dollies, glides, or 1/8" Masonite with the shiny side down. Rolling appliances or heavy load bearing carts with small wheels directly across the floor may damage the vinyl floor.
- To prevent indentations and scratches remove small diameter buttons/ends from furniture legs and replace with non-staining floor protectors with a surface no less than 1" in diameter.

