

Distributed by Bamboo-Design.ca

# Cut Costs, Not Corners



#### **Build Expansively**

Designed with professional-grade durability, Vinyl Select XL offers longer, broader luxury vinyl planks, perfect for fast home or commercial upgrades. A 100% waterproof construction, rapid click-lock milling, and strengthening limestone composite core make flooring easy to install and clean in any room without the need for glue, nails, or acclimation. An ultra-thick 20mil wear layer delivers scratch protection while built-in acoustic padding provides boosted sound insulation. Not one to sacrifice brawn for beauty, the XL collection also boasts rich hardwood visuals so authentic you'll wonder if you're standing on actual timber.

## **Available Colors**




















### Ready, Set, Get Wet

100% waterproof planks are exactly that, meaning Vinyl Select XL can be installed in every room including kitchens, bathrooms, and basements. This also makes for easy cleaning!

# **Go Long**

The XL collection's longer, wider planks make rooms feel more expansive, open, and modern. Plus, broader boards mean installations go faster, saving time, money, mess, and energy.

#### Bad to the Bone

A backbone of limestone composite within each plank resists indentation and delivers 50% better dimensional stability (less expansion and contraction), requiring no acclimation or transition pieces.

Grain	Light Wood Grain
Plank Length	60"
Plank Width	9"
Plank Thickness	4.7mm
Wear Layer	20mil./ 0.5mm
Attached Pad	1.0mm IXPE
Milling	Rapid Click-Lock
Construction	100% Waterproof (SPC Composite)
Installation Method	Float, Glue
Sound Rating	With CALI Complete: STC 61 & IIC 61 Without Underlayment: STC 61 & IIC 63
Certification	FloorScore® Certified
Indoor Air Quality	Low Emitting VOC & Prop 65 Compliant (VOC and Phthalate Test Results Available Upon Request)
Warranty	50 year residential 15 year commercial
Fire Rating	Class 1
Radiant Heat Compatible	Yes (Up to 85°F)
Weight (lb)	59.53
LEED Points	EQC4.3
Application	Residential, Commercial
Static Coefficient of Friction (ASTM D2047)	Dry:0.78
Resistance to Chemicals (ASTM F925)	Pass
Pass and Resistance to Light (ASTM 1515)	Pass
Temperature Range	0°-140°F

For the most up-to-date specification information, please visit www.CALIfloors.com







